

# LINEA SERIES



**LINEA SERIES** is a new linkable design light with anti-glare and UGR<19. It adopts high lumen efficiency SMD LED with even light output, aluminum light body providing excellent thermal management. Pendant with steel rope, pendant with round ceiling plate, surface mounted, wall mounted, recessed and track installation are all available. With Corner/ Cross/ Straight/ T shaped connectors for multiple shape design. It is mainly used for traditional suspended installation such as workshop, utility rooms, garages and more.

IP40	IK06	220-240V	28-49 WATTS	UGR <19
1-10V	DALI	5 YRS Warranty	LOW GLARE	

## PHYSICAL

Body	Aluminum
Finish	White RAL9016/ Black RAL9005

## OPTICAL

Diffuser	PC(Cover) / PMMA(Lens)
Light Emission	Symmetrical
Beam Angle	UP 110°, Down 75°

## ELECTRICAL

Lamp	LED
Color Rendering	>80
Color Temperature	3000K - 4000K - 5000K
Gear	220-240 VAC   50-60Hz
Ambient Temp.	-20°C ~ 45°C





SUSPENDED WITH OUT CEILING PLATE



TRACK



WALL MOUNTED





SUSPENDED WITH CEILING PLATE



RECESSED



SURFACE MOUNTED



LINEA SERIES

	Rated Power(W)	Light Emission	Lumen(lm)	Dimensions(mm)	Beam Angle
<b>LINEA L1</b>	28W	Direct	3600lm	L1204xW56xH75	75°
<b>LINEA L2</b>	40W	Direct/Indirect	5000lm	L1204xW56xH75	UP 110°, Down 75°
<b>LINEA L3</b>	35W	Direct	4600lm	L1504xW56xH75	75°
<b>LINEA L4</b>	49W	Direct/Indirect	6200lm	L1504xW56xH75	UP 110°, Down 75°

## ORDERING CODE

SERIES NAME - PRODUCT RANGE - BODY FINISH - CCT - CONTROL - ACCESSORIES

LINEA	1.1	W WHITE	30 3000K	1 ON-OFF	S1 SUSPENDED WITH OUT CEILING PLATE
	1.2	B BLACK	40 4000K	2 1-10V	S2 SUSPENDED WITH CEILING PLATE
	1.3		50 5000K	3 DALI	T TRACK MOUNTED
	1.4				W WALL MOUNTED
					S SURFACE MOUNTED
					R RECESSED MOUNTED