

QUADRANT BOLLARD



PHYSICAL

Body	Aluminium Extruded Profile
Finish	Polyester Powder Coated

OPTICAL

Di°user	Opal Polycarbonate
Light Emission	Indirect Light Distribution

ELECTRICAL

Lamp	LED
Color Rendering	>80
Color Temperature	3000K-4000K-5000K
Gear	Electronic Included
	220-240 VAC Non-Dimmable Driver
	1-10V or DALI available on request
Operating Temperature	-40°C ~ +50°C
Humidity	10% ~ 90%RH

Power (W)	Lumen(lm)	Dimensions(mm)
10W	1200lm	L120xW120xH1000
20W	2400lm	L135xW135xH1000

L120xW120xH1000



L135xW135xH1000



QUADRANT BOLLARD series stands out as a dependable option for pathways, landscaped areas, and various public spaces, featuring a square frame, complementary column choices, and a four-way light distribution.

-Glare is effectively minimized through a concealed light source.

-The 4 way light distribution not only efficiently illuminates pathways and areas but also introduces a distinctive visual effect.

-Various height options and a coordinating column make it suitable for high-end architectural projects.

-Its minimalistic design ensures seamless integration with diverse architectural styles.

-The bollard is characterized by easy installation and maintenance.

ORDERING CODE

SERIES NAME - PRODUCT RANGE - CCT - CONTROL

QUADRANT	1	30 3000K	1 ON-OFF
BOLLARD	2	40 4000K	2 1-10V
		50 5000K	3 DALI

