

GLOBO



Upon request



PHYSICAL

Body	Aluminum alloy
Finish	Powder Coated
Dimensions	Ø133xH975mm
	Ø133xH500mm

OPTICAL


Diffuser	Clear Polycarbonate (Milky PC cover available)
Light distribution	Assymetric

ELECTRICAL

Lamp	LED
Color Rendering	>80
Color Temperature	3000K-4000K-5000K
Gear	Electronic included 50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Operating Temperature	-30°C - + 45°C
Humidity	10% - 90%RH


GLOBO series serves as an exceptional luminaire for urban settings, suitable for both new construction projects and retrofit applications. This versatile bollard light is available in heights of 0.5M and 1M.

- 360° Coverage and visual comfort.
- High lumen output efficiency, up to 130lm/W.
- The housing is made of 100% aluminum alloy.
- Outdoor powder coating for anti-corrosion.
- Easy to maintain.
- Robust design with IK10 protection.




Range	Power(W)	Lumen(lm) MILKY PC COVER	Lumen(lm) CLEAR OPTIC LENS
EQUILIBRIUM 1	14W	1400lm	1820lm
EQUILIBRIUM 2	25W	2500lm	3250lm

AVAILABLE OPTICS



MILKY PC COVER
LOW GLARE



CLEAR OPTIC
LENS

ORDERING CODE

SERIES NAME - PRODUCT RANGE - CCT - OPTICS - CONTROL

GLOBO 1 30 3000K M MILKY 1 ON-OFF
2 40 4000K C CLEAR 2 1-10V
50 5000K 3 DALI