

KOOT GRAZER ROUND



IP67	IK08	24Vdc	5 YRS Warranty	10 WATTS
------	------	-------	----------------	----------

Upon request

1-10V	DALI	DMX	MONO COLOR	RGB	RGBW
-------	------	-----	------------	-----	------

PHYSICAL

Body	Aluminum 6063
Finish	Epoxy coating or anodized
Screws	Stainless Steel 316L
Gasket	Silicone rubber
Dimensions	L1000xW50xH44 mm

OPTICAL

Diffuser	3mm Ultra-clear glass
Beam Angle	10°,15°,30°,45°,60°,15x45°,10x60°
Bracket	Adjustable
CRI	>90


ELECTRICAL

Lamp	LED
Lumen	900 lm
Color Temperature	3000K, 4000K, 5000K, RGB
Gear	24Vdc (remote driver to be ordered separately)
Ambient Temp.	-25°C ~ 50°C
Ambient Humidity	10% - 90%
Lamp Life	50,000 h

KOOT GRAZER ROUND consists of a range of LED sources to deliver the desired light effect to façades, columns, bridges, monuments, and signs. The LEDs used come in 3 different tones of white, as well as blue, red, green, amber and RGB. Several lenses from 10° till 60° are available.

THERMAL MANAGEMENT

All fixtures are designed to withstand ambient temperatures of at least 50 °C. The LEDs are mounted on metal core PCBs with excellent heat conductivity aluminum coefficient of heat conductivity $\geq 2.0\text{w/mk}$.



ORDERING CODE

SERIES NAME - CCT - OPTICS - CONTROL

KOOT GRAZER ROUND	30 3000K	10 10°	1 ON-OFF
	40 4000K	15 15°	2 DALI
	50 5000K	30 30°	3 DMX512
	RGB	45 45°	
		60 60°	
		1545 15x45°	
		1060 10x60°	