

# DAHLIA SERIES



IP20	220-240V	5 YRS Warranty	10-30 WATTS
------	----------	-------------------	----------------

Upon request

1-10V	DALI
-------	------

## PHYSICAL

Body	Die cast Aluminum
Finish	Polyester Powder Coated

## OPTICAL

Diffuser	Polycarbonate
Reflector	Polycarbonate
Aiming	355° Rotatable horizontally
	325° Adjustable vertically
Beam Angle	39°

## ELECTRICAL

Light source	LED CREE
CRI	>80 (>90 available on request)
CCT	3000K-4000K-6000K
Driver	Electronic included   50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request

**DAHLIA SERIES** is a recessed mounted downlight with asymmetric beam design. The aluminum die-casting frame with white powder coating finishing provides an excellent thermal management. It adopts SMD light source, high lumen and high CRI offers a uniform light output. It could offer a special light spot, users will have a great visual enjoyment.

Range	Rated Power(W)	Dimensions(mm)	Cut-out Dimensions(mm)
DAHLIA 1.1	10W	Ø85xH70	Ø75
DAHLIA 1.2	18W	Ø108xH85	Ø95
DAHLIA 1.3	30W	Ø135xH97	Ø125



## ORDERING CODE

SERIES NAME - PRODUCT RANGE - CCT - OPTICS - CONTROL

DAHLIA	1.1	30 3000K 39 39°	1 ON-OFF
	1.2	40 4000K	2 1-10V
	1.3	60 6000K	