

KOOT BLADE



| | | | | |
|------|------|-------|-------------------|-------------|
| IP67 | IK08 | 24Vdc | 5 YRS Warranty | 30 WATTS |
|------|------|-------|-------------------|-------------|

Upon request

| | | | |
|-------|------|-----|--|
| 1-10V | DALI | DMX | |
|-------|------|-----|--|

PHYSICAL

| | |
|------------|------------------------------------|
| Body | Aluminium Extruded Profile |
| Finish | Anodized oxidation & double coated |
| Dimensions | L475xW75xH90mm |


OPTICAL

| | |
|--------------------|---------------------------|
| Diffuser | Tempered glass |
| Light Distribution | 3x180° blade effect optic |

ELECTRICAL

| | |
|-----------------------|---|
| Light source | LED |
| Lumen | 900lm |
| CRI | >80 |
| CCT | 3000K-4000K-5000K |
| Remote Driver | Constant voltage 24V DC remote driver needed 1-10V or DALI available on request |
| Operating Temperature | -40°C - +50°C |
| Humidity | 10% - 90%RH |

KOOT BLADE is a recessed luminaire with 180° light emissions, an ideal lighting solution for arches and windows. This type of luminaire is designed to be installed inside a recessed area, providing a sleek and seamless appearance that complements the architecture of the space. The 180° light emission ensures that light is evenly distributed in all 3 directions, effectively illuminating the entire surrounding area. This feature is especially useful for arches and windows, as it can provide a soft and diffused glow that accentuates the curves and contours of these architectural elements. Additionally, a recessed luminaire with 180° light emissions can be used to create a dramatic effect by highlighting the texture and details of the surrounding surfaces, adding depth and dimension to the space.



ORDERING CODE

SERIES NAME - CCT - CONTROL

| | | |
|------------|----------|----------|
| KOOT BLADE | 30 3000K | 1 ON-OFF |
| | 40 4000K | 2 1-10V |
| | 50 5000K | 3 DALI |
| | RGB RGB | |

