

OLEANDER SERIES



OLEANDER SERIES single head and double head provided for wide choice. Adjustable lighting direction offers various lighting orientation. OLEANDER is a recess-mounted LED that offers outstanding lumen packages for spaces that require a large amount of light. This luminaire is indicated for lighting from high ceilings and for retail stores due to its adjustable factor.



Upon request



PHYSICAL

Body	Die cast Aluminum
Finish	Polyester Powder Coated

OPTICAL

Diffuser	Polycarbonate
Reflector	Polycarbonate
Aiming	355° Rotatable horizontally 325° Adjustable vertically
Beam Angle	15°,24°,36°

ELECTRICAL

Light source	LED CREE
Efficacy	93lm/W
CRI	>80 (>90 available on request)
CCT	3000K-4000K-6000K
Driver	Electronic included 50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Light source Life	60,000 h

OLEANDER ROUND



OLEANDER SQUARE



OLEANDER DUAL



PRODUCT RANGE

	Rated Power(W)	Lumen(lm)	Dimensions(mm)	Cut out Dimensions(mm)
OLEANDER ROUND 1.1	12W	1116lm	Ø90xH80	Ø75mm
OLEANDER ROUND 1.2	20W	1860lm	Ø110xH105	Ø95mm
OLEANDER ROUND 1.3	30W	2790lm	Ø135xH140	Ø115mm
OLEANDER SQUARE 1.1	12W	1116lm	L90xW90xH80	80x75mm
OLEANDER SQUARE 1.2	20W	1860lm	L117xW117xH105	95x90mm
OLEANDER SQUARE 1.3	30W	2790lm	L140xW140xH125	120x115mm
OLEANDER DUAL 1.1	2x12W	2x1116lm	L170xW90xH80	152x75mm
OLEANDER DUAL 1.2	2x15W	2x1400lm	L210xW117xH105	185x95mm
OLEANDER DUAL 1.3	2x20W	2x1860lm	L210xW117xH105	185x95mm
OLEANDER DUAL 1.4	2x30W	2x2790lm	L250xW140xH125	120x225mm

ORDERING CODE

SERIES NAME - PRODUCT RANGE - BODY FINISH - CCT - OPTICS - CONTROL

OLEANDER	ROUND 1.1	W WHITE	30 3000K 15 15°	1 ON-OFF
	ROUND 1.2	B BLACK	40 4000K 24 24°	2 I-10V
	ROUND 1.3		60 6000K 36 36°	3 DALI
	SQUARE 1.1			
	SQUARE 1.2			
	SQUARE 1.3			
	DUAL 1.1			
	DUAL 1.2			
	DUAL 1.3			
	DUAL 1.4			