

QATAF SERIES



PHYSICAL

Body	Stainless Steel 316L
Frame	Stainless Steel 316L
Recessing tube	Polycarbonate

OPTICAL

Diffuser	Polycarbonate
Light Emission	Mono, Dual, Quadro, Multi
CRI	>80

ELECTRICAL

CCT	3000K - 4000K
Driver	Integrated LED driver 220-240V 50/60Hz
Ambient Temp.	-25°C - 50°C
Ambient Humidity	10% - 90%

QATAF series is a range of compact recessed marker lights, with an IP67 protection rating. The power supply is built into the structure, so they can be connected directly to the power line, making installation easier. The body is made of AISI 316 L steel with lateral light emission to indicate pathways and pedestrian zones.

The luminaries are available with different light sectors for various on-site lighting situations. The light from the luminaries is directed immediately above ground level onto the surface to be illuminated, thus illuminating walkways and traffic areas or highlighting potential hazards such as stairs and steps.



QATAF 1
MONO









QATAF 2
DUAL

QATAF 3
QUADRO

QATAF 4
MULTI

QATAF 5
MONO

QATAF 6
DUAL



PRODUCT RANGE

	Rated Power(W)	Lumen(lm)	Dimensions(mm)	LED Quantity(pcs)	Beam angle
QATAF 1	3W	30lm	Ø90xH92	1 pcs	60°
QATAF 2	4W	40lm	Ø90xH92	2 pcs	2x60°
QATAF 3	4W	40lm	Ø90xH92	4 pcs	4x60°
QATAF 4	4W	40lm	Ø90xH92	4 pcs	12x15°
QATAF 5	10W	150lm	Ø105xH115	1 pcs	5°,15°,30°,60°
QATAF 6	10W	150lm	Ø105xH115	2 pcs	2x5°,2x15°,2x30°,2x60°

ORDERING CODE

SERIES NAME - PRODUCT RANGE - CCT - OPTICS - CONTROL

QATAF	1	30 3000K	Refer to	I ON-OFF
	2	40 4000K	above table	
	3			
	4			
	5			
	6			