

QUADRO SERIES



Upon request



PHYSICAL

Body	Steel
Finish	White
Dimensions	L595xW595xH54
	L1195xW295xH54

OPTICAL

Diffuser	Polycarbonate
Light Emission	Direct
Beam Angle	130°

ELECTRICAL

Light source	LED
Lumen	Square: 3380lm / Rectangle: 3280lm
CRI	>80
CCT	3000K - 4000K - 5000K - 5700K
Driver	Electronic included 50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Ambient Temp.	-10°C ~ 45°C

QUADRO SERIES is a new LED panel light that adopts secondary optical design. The PMMA optic lens combined with

special designed PC shade can achieve a more uniform light and larger emitting area, so that users can enjoy more comfortable visual experience. Powder spraying surface treatment is employed in the Light source fixture which makes the Light source corrosion resistant. Designed for grid ceiling commercial applications such as offices & schools, shopping centers, super markets, retailer shops, hospitals, laboratory, dust-free workshop etc.



L1195xW295xH54

ORDERING CODE

SERIES NAME	PRODUCT RANGE	CCT	CONTROL
QUADRO	1	30 3000K	1 ON-OFF
	2	40 4000K	2 1-10V
	3	50 5000K	3 DALI
		57 5700K	

