

ASTER SERIES



IP20	220-240V	5 YRS Warranty	10-40 WATTS	LOW GLARE	UGR <19
------	----------	-------------------	----------------	--------------	------------

Upon request

1-10V	DALI
-------	------

PHYSICAL

Body	Aluminum
Finish	White/ Black

OPTICAL

Aiming	16°,30°,45°
Diffuser	Polycarbonate
CRI	>80

ELECTRICAL

Light source	LED CREE
Power	10W,22W,30W,40W
Efficacy	100lm/W
CCT	3000K, 4000K, 6000K
Driver	220-240Vac
Ambient Temp.	-30°C - +45°C
Ambient Humidity	10% - 90%
Light source Life	60,000 h

ASTER SERIES is a downlight with larger rotation angle so that it can meet more lighting direction demands. It can be vertically rotated to 90 degrees to the extent that the light emitting surface of the lamp is completely perpendicular to the installation plane, horizontally rotated 350 degree to meet more lighting direction demands.

It is designed for general lighting applications in offices, supermarkets, shops, schools, hotels, etc. It is also widely used for public areas, such as stairways, lobbies, receptions, corridors etc.

Range	Power (W)	Lumen (lm)	Dimensions (mm)	Cut-out Dimensions (mm)
ASTER 1	10W	1000lm	Ø90xH76mm	Ø85mm
ASTER 2	22W	2200lm	Ø108xH96mm	Ø95mm
ASTER 3	30W	3000lm	Ø138xH129mm	Ø125mm
ASTER 4	40W	4000lm	Ø165xH129mm	Ø150mm

ORDERING CODE

SERIES NAME - PRODUCT RANGE - FINISH - CCT - OPTICS - CONTROL

ASTER	1	W WHITE	30 3000K	15 15°	1 ON-OFF
	2	B BLACK	40 4000K	30 30°	2 1-10V
	3		60 6000K	45 45°	3 DALI
	4				