

MAGNOLIA SERIES



IP20	220-240V	5 YRS Warranty	5-20 WATTS	LOW GLARE	UGR <16
------	----------	-------------------	---------------	--------------	------------

Upon request

1-10V	DALI
-------	------

PHYSICAL

Body	Aluminum
Finish	White/ Black

OPTICAL

Aiming	12°,24°,35°
Diffuser	Polycarbonate
CRI	>80

ELECTRICAL

Light source	LED CREE
Power	5W,10W,15W,20W
Efficacy	91lm/W
CCT	3000K, 4000K
Driver	220-240Vac
Ambient Temp.	-30°C - +50°C
Ambient Humidity	10% - 90%
Light source Life	60,000 h

MAGNOLIA SERIES is an anti-glare downlight, it adopts high lumen light source, deep reflector and low glare UGR<16, which provides a comfortable visual experience. The aluminum profile provides excellent thermal dissipation and ensures a long lifespan. DALI, 1-10V driver are available to provide excellent dimming effect.

It is designed for general lighting applications in offices, schools, hotels etc. It is also widely used for public areas, such as stairway, lobby, reception, corridors etc.

MAGNOLIA LE 85lm/W					
	Rated Power(W)	Lumen (lm)	LED	Dimensions (mm)	Cut-out Dim(mm)
MAGNOLIA 1 LE	5W	425 lm	CREE	Ø55xH75mm	Ø50mm
MAGNOLIA 2 LE	10W	850 lm	CREE	Ø75xH106mm	Ø68mm
MAGNOLIA 3 LE	15W	1275 lm	CREE	Ø91H120mm	Ø82mm
MAGNOLIA 4 LE	20W	1700 lm	CREE	Ø128H130mm	Ø118mm

MAGNOLIA HE 100lm/W					
	Rated Power(W)	Lumen (lm)	LED	Dimensions (mm)	Cut-out Dim(mm)
MAGNOLIA 1 HE	5W	500 lm	BRIDGELUX	Ø55xH75mm	Ø50mm
MAGNOLIA 2 HE	10W	1000 lm	BRIDGELUX	Ø75xH106mm	Ø68mm
MAGNOLIA 3 HE	15W	1500 lm	BRIDGELUX	Ø91H120mm	Ø82mm
MAGNOLIA 4 HE	20W	2000 lm	BRIDGELUX	Ø128H130mm	Ø118mm

ORDERING CODE

SERIES NAME - PRODUCT RANGE - FINISH - CCT - OPTICS - CONTROL

MAGNOLIA	1 LE	W WHITE	30 3000K	12 12°	1 ON-OFF
	2 LE	B BLACK	40 4000K	24 24°	2 1-10V
	3 LE			35 35°	3 DALI
	4 LE				
	1 HE				
	2 HE				
	3 HE				
	4 HE				